

# MAXUFLEX CATALOGUS HARDWARE & DIY 2018 - 3

MAXUFLEX SNELKOPPELINGEN

TYPE-N

RACCORDS RAPIDES MAXUFLEX

RECTUS COMPATIBEL

RECTUS COMPATIBLE

Luchtconsumptie / Consommation d'air:

1100 L/min

Maximum druk / Pression maximale:

35 bar



MAXUFLEX-RN 2-WEG + SNELKOPP. - VR.

DÉRIVAT. 2-POINTS + RACC. RAPIDE - FEM.

Referentie	Model/Modèle	pcs	EAN
6015 02S 038	3 x 3/8" BSP	50	5415197017024
6015 02S 012	3 x 1/2" BSP	50	5415197017031



MAXUFLEX-RN 3-WEG - NAAKT - VROUW.

DÉRIVATION 3-POINTS - NUE - FEM.

Referentie	Model/Modèle	pcs	EAN
6015 004 038	4 x 3/8" BSP	50	5415197017048
6015 004 012	4 x 1/2" BSP	50	5415197017055



MAXUFLEX-RN 3-WEG + SNELKOPP. - VR.

DÉRIVAT. 3-POINTS + RACC. RAPIDE - FEM.

Referentie	Model/Modèle	pcs	EAN
6015 03S 038	4 x 3/8" BSP	50	5415197017062
6015 03S 012	4 x 1/2" BSP	50	5415197017079



MESSING SLANGPILAAR - MANN.

TULLE + FILETAGE - MALE

Referentie	Afmeting/Dimension	pcs	EAN
6005 145 0614	1/4" x 6mm	10	5415197010711
6005 145 0814	1/4" x 8mm	10	5415197010728
6005 145 1014	1/4" x 10mm	10	5415197010735
9200 25/0SK	3/8" x 10mm	10	4015933026627
9200 75/1SKSB	1/2" x 13mm	10	4015933002720