



Maxuflex Air F20 ISO - M20 - SBR - D

Inwendig: SBR
 Kleur: Zilvergrijs
 Uitwendig: SBR
 Kleur: Zwart

Innen: SBR
 Farbe: Silbermetallic
 Aussen: SBR
 Farbe: Schwarz

Inside: SBR
 Colour: Silver metallic
 Outside: SBR
 Colour: Black

Rubber perslucht slang, zwart glad.

- knikvast en flexibel
- bestand tegen oliesporen
- goede verouderings- en weerbestendigheid
- conform ISO 2398

Gummi Pressluftschlauch schwarz, glatt.

- knickfest und flexibel
- beständig gegen Ölsuren
- gute Alterungs und Witterungsbeständigkeit
- entspricht ISO 2398

Rubber air hose black smooth.

- good flexibility and kink resistance
- resistant to oil traces
- ageing and weather resistant
- acc. ISO 2398

Artikel Nr Artikel Nr Article Nr	Binnen Innen inside Ø mm	Buiten Aussen Outside Ø mm	Buigstr. Biegerad. Bendrad. mm	Vakuum Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m
M10LAI0006	6.0	12.0	60		140
M10LAI0008	8.0	15.0	80		170
M10LAI0010	10.0	18.0	100		280
M10LAI0013	13.0	22.0	130		390

Normen / Standards:
ISO 2398

Temperatuurbereik (zie medium)
 Temperaturbereich (siehe Medium)
 Temperature range (see media)
 -25 °C +70 °C

Werkdruk
 Betriebsdruck
 Working Pressure
 20 bar

Barstdruk
 Platzdruck
 Burst Pressure
 80 bar

Markering / Markierung / Branding:
 AIR WATER WP 20 BAR BP 80 BAR ISO 2398
 DIA

Lengten / Längen / Lengths:
 40 - 50 - 100 m