



Maxuflex Hydraulic UHP 3315 - M1034 - BESNO NYLON 11 P40 LTO - D

Inwendig: BESNO NYLON 11 P40 LTO
 Kleur: Transparant
 Uitwendig: URETHANE
 Kleur: Zwart

Innen: BESNO NYLON 11 P40 LTO
 Farbe: Transparent
 Aussen: URETHANE
 Farbe: Schwarz

Inside: BESNO NYLON 11 P40 LTO
 Colour: Translucent
 Outside: URETHANE
 Colour: Black

Ultra hogedruk slang voor:

- Hydraulische flying leads
- werkt via umbilical component
- BOP bundle component
- hot lines en chemische injectie
- waterinjectie
- naadloos Besno nylon 11 P40 TLO core slang
- versterkt met aramide vezels
- glad urethane hoes
- API 17E geschikt voor de meeste afmetingen
- beschikbaar in doorlopende lengtes > 3000 m
- beschikbaar als enkel lijns- of in bundelcomponent
- geleverd met 316 roestvrij stalen fittings voor PSTD 3315

Ultra high pressure hose for :

- hydraulic flying leads
- work over umbilical component
- BOP bundle component
- hot lines and chemical injection
- water injection
- seamless Besno nylon 11 P40 TLO core tube
- aramide fiber reinforcement
- smooth urethane jacket
- API 17E compliant for most sizes
- available in continuous lengths > 3000 m
- available as single line or bundle component
- supplied with 316 stainless steel fittings to PSTD 3315

Artikel Nr	Binnen	Buiten	Buigstr.	Vakuum	Gewicht
Artikel Nr	Innen	Aussen	Biegerad.	Vakuum	Gewicht
Article Nr	inside	Outside	Bendrad.	Vacuum	Weight
	Ø mm	Ø mm	mm	Bar	gr/m
M3315 006 3000	6.35	14.9	203		150

Normen / Standards:
 API 17E, GP 65-06-03, GP 65-05-06

Temperatuurbereik (zie medium)
 Temperaturbereich (siehe Medium)
 Temperature range (see media)
 -40 °C +72 °C

Werkdruk Betriebsdruck
 Working Pressure 1034 (15K) bar

Barstdruk Platzdruck
 Burst Pressure 2758 (40K) bar

Markering / Markierung / Branding:
 BRANDNAME

Lengten / Längen / Lengths:
 up to 3000 m