



# Maxuflex Hydraulic UHP 3390 - M689 - BESNO NYLON 11 P40 LTO - D

Inwendig: BESNO NYLON 11 P40 LTO  
 Kleur: Transparant  
 Uitwendig: URETHANE  
 Kleur: Zwart

Innen: BESNO NYLON 11 P40 LTO  
 Farbe: Transparent  
 Aussen: URETHANE  
 Farbe: Schwarz

Inside: BESNO NYLON 11 P40 LTO  
 Colour: Translucent  
 Outside: URETHANE  
 Colour: Black

Ultra hogedruk slang voor hydraulische flying leads.

- werkt via umbilical component
- BOP bundle component
- hot lines en chemische injectie
- waterinjectie
- naadloos Besno nylon 11 P40 TLO core slang
- versterkt met aramide vezels
- glad urethane hoes
- API 17E geschikt voor de meeste afmetingen
- beschikbaar in doorlopende lengtes > 3000 m
- beschikbaar als enkel lijns- of in bundelcomponent
- geleverd met 316 roestvrij stalen fittings voor PSTD 3394-3395

Ultra high pressure hose for :

- hydraulic flying leads
- work over umbilical component
- BOP bundle component
- hot lines and chemical injection
- water injection
- seamless Besno nylon 11 P40 TLO core tube
- aramide fiber reinforcement
- smooth urethane jacket
- API 17E compliant for most sizes
- available in continuous lengths > 3000 m
- available as single line or bundle component
- supplied with 316 stainless steel fittings to PSTD 3394-3395

Artikel Nr	Binnen	Buiten	Buigstr.	Vakuum	Gewicht
Artikel Nr	Innen	Aussen	Biegerad.	Vakuum	Gewicht
Article Nr	inside	Outside	Bendrad.	Vacuum	Weight
	Ø mm	Ø mm	mm	Bar	gr/m
M3390 006 3000	6.35	14.9	203		150
M3390 009 3000	9.5	19.4	254		228

Normen / Standards:  
 API 17E, GP 65-06-03, GP 65-05-06

Temperatuurbereik (zie medium)  
 Temperaturbereich (siehe Medium)  
 Temperature range (see media)  
 -40 °C +72 °C

Werkdruk Betriebsdruck  
 Working Pressure 689 (10K) bar

Barstdruk Platzdruck  
 Burst Pressure 2758 (40K) bar

Markering / Markierung / Branding:  
 BRANDNAME

Lengten / Längen / Lengths:  
 max 3000 m