



# Maxuflex Hydraulic Control Connection 3000 - M207 - NBR - D

Inwendig: NBR  
 Kleur: Zwart  
 Uitwendig: NBR  
 Kleur: Zalm rood

Innen: NBR  
 Farbe: Schwarz  
 Aussen: NBR  
 Farbe: Lachs rot

Inside: NBR  
 Colour: Black  
 Outside: NBR  
 Colour: Salmon red

Hydraulische controle connectie die gebruikt wordt in broncontrole systemen voor boringen en exploratie platforms op het vasteland, getest op ontvlambaarheid.

- versterkt met twee stalen gebreide draden
- binnenste buis olie resistent NBR
- cover oliebestendig en slijtvastheid CR, getest op ontvlambaarheid
- speciale assemblageprocedure vereist
- onafhankelijk getest volgens Lloyd Register Fire Tests for Flexible Hoses on Offshore Installations. Register Fire Tests for Flexible Hoses on Offshore Installations (OD/1000/499-29th June, 1992) and EUB (Directive 036)
- ook geschikt voor toepassingen waar brandveilig geteste hydraulische slangen vereist zijn

Hydraulic control connection that is used in well control system on land based drilling and exploration rigs, fire tested

- reinforcements : two steel wire braids
- inner tube oil resistant NBR
- cover oil and abrasion resistant CR, fire tested
- special assembly procedure required.
- independently tested per Lloyd Register Fire Tests for Flexible Hoses on Offshore Installations. Register Fire Tests for Flexible Hoses on Offshore Installations (OD/1000/499-29th June, 1992) and EUB (Directive 036)
- also suitable for applications where fire tested hydraulic hose is required

Artikel Nr	Binnen	Buiten	Buigstr.	Vakuum	Gewicht
Artikel Nr	Innen	Aussen	Biegerad.	Vakuum	Gewicht
Article Nr	inside	Outside	Bendrad.	Vacuum	Weight
	Ø mm	Ø mm	mm	Bar	gr/m
M3000-06 009	9.5	28.2	152		1120
M3000-08 012	12.7	30.2	203		1210
M3000-12 019	19.1	37.8	279		1820
M3000-16 025	25.4	46.7	381		2560

Normen / Standards:  
 OD/1000/499-29th June, 1992 - EUB036

Temperatuurbereik (zie medium)  
 Temperaturbereich (siehe Medium)  
 Temperature range (see media)  
 -40 °C +100 °C

Werkdruk  
 Betriebsdruck  
 Working Pressure  
 207 bar

Barstdruk  
 Platzdruck  
 Burst Pressure  
 827 bar

Markering / Markierung / Branding:  
 BRANDNAME + 3/8" (9.5mm)  
 W.P. 3000 psi (20,7 MPa)

Lengten / Längen / Lengths:  
 assembled hose only